

OVERSIZED WOODGRIP FASTENERS

#14 AND #17 "GOOF SCREWS"



DESCRIPTION:

Self tapping fasteners are designed to attach both metal to wood and metal to metal: Commonly used to replace old rusted or worn fasteners that have a smaller diameter shank.

- #14 Diameter for replacing smaller diameter screws (#9, #10, #12).
- #17 Diameter for replacing smaller diameter screws (1/4" #14 or smaller)
- Assembled with a bond seal washer for a consistent, weather tight seal and improved installation appearance
- #14 x 1 1/2" Woodgrips feature a Milled cut point to tap into 29GA, 26GA or 24 GA panels
- Type A /AB/or B available.
- Available painted to match your metal panel color

SPECIFICATIONS:

SPECIFICATIONS	TYPE
WASHER	EPDM WASHER
COATING/ RUST PROTECTION	ZINC PLATED AVAILABLE W/SENTRI
APPLICATION	METAL TO WOOD/METAL TO METAL
POINT	A OR B OR MILLED POINT
HEAD/DRIVER REQUIRED	5/16" HWH OR 3/8" HEX HEAD

SIZES:

AVAILABLE SIZES INCLUDE :

5/16 HWH #14 X 1" *MP , #14 X 1 1/2" *MP (*MP) MILLED POINT

3/8" HH: #14 X 1" AB, #14 X 1 1/4" AB, #14 X 1 1/2" AB,

3/8" HH: #17 X 3/4" AB, #17 X 1" AB, #17 X 1 1/2" AB

INSTALLATION:

TOOLS: 0 – 600 RPM SCREW DRIVER EQUIPED WITH DEPTH SENSING NOSE PIECE

INSTOCK SIZES AND COLORS:

#14 X 1 1/2" MP MILL INSTOCK IN FLORIDA WAREHOUSE.

OTHER SIZES IN STOCK IN GEORGIA WAREHOUSE.

SCREWS ARE PAINTED AT TIME OF ORDER.

#14 TYPE A MILLED POINT

PULL OUT WOOD SPRUCE , PINE, FIR	PULL OUT PLYWOOD 1" SPF : 1013	PULL OUT OSB	PULL OVER
			22 GA : 1097
			24 GA : 810
-			26 GA : 564

SEE: NOTES IN CATALOG