

PANCAKE HEAD/ STANDING SEAM FASTENERS



DESCRIPTION:

Designed with unique head styles, drill point configurations and material types to meet performance requirements to attach standing seam roof clips and panels.

- Low profile head preventing panel damage from fastener head contact
- Torque drive control for uniform installation appearance
- Available with (type A) sharp point, and (SD) #1 drill point.
- Available in Zinc plated or 300 series stainless steel

SPECIFICATIONS:

SPECIFICATIONS	TYPE
WASHER	NONE
COATING/ RUST PROTECTION	ZINC PLATED OR STAINLESS STEEL
APPLICATION	STANDING SEAM METAL ROOFING
POINT	TYPE A POINT , OR SELFDRILL POINT
HEAD/DRIVER REQUIRED	#2 PHILLIPS FOR ZINC , SQUARE DRIVER FOR STAINLESS STEEL

AVAILABLE SIZES: #10 DIAMETER

ZINC PLATED TYPE "A"	#10 X 1", #10 X 1 1/2", #10 X 2"
STAINLESS TYPE "A"	#10 X 1", #10 X 1 1/2"
ZINC PLATED SD	#10 X 1", #10 X 2"

INSTALLATION:

TOOLS: 0 – 1800 RPM SCREW DRIVER EQUIPED WITH DEPTH SENSING NOSE PIECE

INSTOCK SIZES:

ZINC PLATED TYPE "A"	#10 X 1", #10 X 1 1/2", #10 X 2"
STAINLESS TYPE "A"	#10 X 1" SQ, #10 X 1" PH
ZINC PLATED SD	#10 X 1"

SPECIFICATIONS:

#10 X 1" TYPE "A"

PULL OUT PLYWOOD	PULL OUT OSB
3/4" : 615	23/32" : 355
5/8" : 521	19/32" : 290

SEE: NOTES IN CATALOG

#10 X 1" SELF DRILL SD

PULL OUT
12 GA (.105) : 1782
14 GA (.075) : 1072
16 GA (.060) : 782